

ELEMENTS® BACK

HCPCS CODING: E2611/E2612
GENERAL USE BACK



PRODUCT FEATURES

- + Strapping system can accommodate for kyphosis and provide lumbar support.
- + 1" pressure relieving foam provides a more comfortable back support than a standard sling back.
- + Back securely installs directly over wheelchair canes.
- + Steel D-rings provide superior strength and durability.
- + One SKU fits wheelchair sizes 16"- 21"; second SKU fits wheelchair sizes 22"-26"
- + Free custom logo patch program available. *See details below

COLLAPSIBLE BACK FOR FOLDING WHEELCHAIRS

- Installation is made easy with a durable strapping system.
- The Elements Back design allows the entire backrest to fold with the wheelchair for easy transportation and storage.



ADJUSTABLE TENSION STRAPPING SYSTEM

- Innovative strapping system can accommodate for kyphosis and provide lumbar support.
- Using hook and loop attachment, the back tension is easily adjustable to fit the needs specific users.



COVER OPTIONS



STRETCH-AIR FABRIC: designed for air transmission and heat dissipation. This breathable laminate combines a high-stretch polyester top layer with a waterproof, breathable vapor barrier.



COMFORT-TEK FABRIC: the fluid proof exterior has supple leathery properties that provide an easily cleaned surface and protection for the inner cushion. Comfort-Tek has multi-dimensional stretch and helps alleviate pressure on bony prominences.

FREE CUSTOM PATCHES

CUSTOM COMPANY PATCH:

The Elements back is available with a custom patch featuring both your company logo and phone number added free of charge.

Contact a Customer Service representative for details or additional information. 1-800-564-9248

**Minimum order quantities apply.*



YOUR LOGO HERE

STANDARD ELEMENTS BACK

16 INCHES TALL

stretch-air part #	comfort-tek part #	height	wc size	wt. limit
BKSTRPS-1521	BKSTRPF-1521	16"	16 - 21	250 lbs.
BKSTRPS-2129	BKSTRPF-2129	16"	22 - 26	350 lbs.

LOW ELEMENTS BACK

10 INCHES TALL

stretch-air part #	comfort-tek part #	height	wc size	wt. limit
BKSTRPSL-1521	BKSTRPFL-1521	10"	16 - 21	250 lbs.
BKSTRPSL-2129	BKSTRPFL-2129	10"	22 - 26	350 lbs.